

37

Claim 43. (Amended) An oscillating transmission having an output gear, said output gear being mounted for rotation in either direction, a gear cage having a first drive gear and a second drive gear for alternately driving said output gear to oscillate said output gear between a first and second angular position, means mounting said gear cage for movement between a first and second drivingly engaged position, toggle means for alternately moving said gear cage in one direction to said first drivingly engaged position to drivingly engage said first drive gear with said output gear to drive said output gear in a direction to its second angular position and in the other direction to said second drivingly engaged position to drivingly engage said second drive gear with said output gear to drive said output gear in a direction to its first angular position, [said means for alternately moving said gear cage including] first biasing means for alternately biasing said toggle means and gear cage in one direction to the other toward [to] its first or second drivingly engaged position, [said] means for [alternately moving said gear cage] removing the bias of said first biasing means from said gear cage during the movement of said output gear to its first or second angular position, and second biasing means for directly biasing said gear cage in said one direction towards its first drivingly engaged position to maintain the gear cage biased in said one direction when the bias of said first biasing means [for biasing] has been removed to move said gear cage in said other direction at least until said first biasing means is biasing said gear cage in said other direction.

Claim 63, last line, after "positions", insert --until engagement--.

Claim 69, last line, after "positions", insert --until engagement--.

9798

Cancel claim 75, because the amendment herein to claim 63 makes claim 75 a duplicate of claim 63.

Please add new claims 102 - 174.

⁹⁰
CLAIM ~~102~~. An oscillating sprinkler unit, comprising:

a sprinkler head mounted for rotation about a first axis;

a drive motor;

E4
a reversible gear train for drivingly connecting said drive motor for driving said sprinkler head in alternate directions, comprising drive gear means connected to said sprinkler head, shiftable drive means comprising alternately operable terminal gear means and carrier means for carrying said terminal gear means, said shiftable drive means being shiftable to alternately engageable positions of said alternatively operable terminal gear means with said drive gear means for driving said sprinkler head in alternate directions;

shifting arm means pivotally mounted adjacent said carrier means and movable between alternate shifting positions by engagement with contact means carried by said drive gear means, and lost motion means for connecting said shifting arm means with said carrier means for shifting said carrier means between said alternately engageable positions upon movement of said shifting arm means between said alternate shifting positions;

first over-center biasing means for maintaining said carrier means in a selected one of said alternately engageable positions until positively shifted therefrom by said shifting arm means; and

second over-center biasing means for maintaining said shifting arm means in a selected one of alternate shifting positions until engagement by said contact means.

⁹¹
CLAIM ~~103~~. The sprinkler of claim ~~102~~ wherein:

said shiftable drive means comprises a drive gear driven by said drive motor
and mounted for rotation about a second axis spaced from said first axis;

said carrier means is mounted for pivotal movement about said second axis;
and

^{E4}
said shifting arm means is mounted for pivotal movement about said first
axis.

⁹²
CLAIM ~~104~~. The sprinkler unit of claim ~~103~~ wherein:

said carrier means comprises a yoke surrounding said first axis, and said lost
motion means comprises contact means on the opposite side of said first axis from
said second axis for alternate engagement with said shifting arm means.

⁹³
CLAIM ~~105~~. The sprinkler unit of claim ~~104~~ wherein:

said first over-center means comprises a spring engaging said yoke.

⁹⁴
CLAIM ~~106~~. The sprinkler of claim ~~105~~ wherein:

said spring comprises a generally U-shaped leaf spring.

⁹⁵
CLAIM ~~107~~. The sprinkler system of claim ~~105~~ wherein:

said first over-center means maintains said terminal gear means in one of said
alternatively operable positions of engagement until said yoke is biased by said
second over-center means through said shifting arm means.

96
CLAIM 108. An oscillating sprinkler unit, comprising:

a sprinkler head mounted for rotation about a first axis;

a drive motor;

E4
a reversible gear train for drivingly connecting said drive motor for driving said sprinkler head in alternate directions, comprising a drive gear connected to said sprinkler head, shiftable drive means comprising alternately operable terminal gear means and carrier means for carrying said terminal gear means, said shiftable drive means being shiftable to alternately engageable positions of said alternatively operable terminal gear means with said drive gear for driving said sprinkler head in alternate directions;

shifting arm means pivotally mounted adjacent said carrier means and movable between alternate shifting positions by engagement with contact means carried by said final drive gear means, and lost motion means for providing engagement with said carrier means for shifting said carrier means between said alternately engageable positions upon movement of said shifting arm means between said alternate shifting positions;

first over-center biasing means for maintaining said carrier means in a selected one of said alternately engageable positions until positively shifted therefrom by said shifting arm means; and

second over-center biasing means for maintaining said shifting arm means in a selected one of alternate shifting positions until engagement by said contact means.

108
101

⁹⁷
CLAIM ~~109~~. The sprinkler of claim ~~108~~ wherein:

said shiftable drive means includes a drive gear driven by said drive motor and mounted for rotation about a second axis spaced from said first axis;

said carrier means is mounted for pivotal movement about said second axis; and

said shifting arm means is mounted for pivotal movement about said first axis.

⁹⁸
CLAIM ~~110~~. The sprinkler unit of claim ~~109~~ wherein:

said carrier means comprises a yoke surrounding said first axis and said lost motion means comprises contact means on the opposite side of said first axis from said second axis;

said over-center means comprises spring means engaging said yoke; and

said spring means comprises a generally U-shaped leaf spring.

⁹⁹
CLAIM ~~111~~. The sprinkler system of claim ~~110~~ wherein:

said first over-center means maintains said terminal gear means in engagement until said yoke is biased by said second over-center means through said shifting arm means.

100

CLAIM ~~112~~. An oscillating sprinkler unit, comprising: a sprinkler head mounted for rotation about a first axis; rotating drive means for driving said sprinkler head in alternate directions; drive means including a shiftable carrier for effecting alternately engageable driving positions with said rotating drive means; arc control contact means; shift means pivotally movable by said arc control contact means for initiating movement of said carrier from one of said alternately engageable driving positions toward the other; first biasing means for biasing said shift means and said shiftable carrier means toward one or the other of said driving positions; and second biasing means for biasing said shiftable carrier into driving engagement with at least one of said alternately engageable driving positions independent of said first biasing means.

34

101

CLAIM ~~113~~. An oscillating sprinkler unit as in claim ~~112~~ wherein:

100

said second biasing means urges said shiftable carrier into one or the other of said alternately engageable driving positions with said rotating drive means until shifted therefrom by said shift means in response to engagement of said shift means by said arc control contact means.

102

CLAIM ~~114~~. An oscillating sprinkler unit as in claim ~~112~~ wherein:

100

each of said first and second biasing means includes over-center spring means.

103

CLAIM ~~115~~. An oscillating sprinkler unit as in claim ~~112~~ wherein:

100

one of said first and second biasing means includes spring means for imposing a load on said shiftable carrier, and the other of said biasing means includes spring means for imposing a load on said shift means.

102
103

¹⁰⁴
CLAIM ~~116~~. An oscillating transmission having an output gear, a gear cage with two drive gears, a first drive gear and a second drive gear for alternate driving engagement with said output gear to oscillate it, means mounting said gear cage for movement, toggle means for alternately moving said gear cage in one direction to drivingly engage said first drive gear with said output gear or in the other direction to drivingly engage said second drive gear with said output gear, first biasing means connected to said toggle means to impose a biasing load on said toggle means and said gear cage in one direction or the other direction and second biasing means connected to said gear cage to impose a biasing load on said gear cage in one direction or the other direction.

¹⁰⁵ ¹⁰⁴
CLAIM ~~117~~. An oscillating sprinkler unit as in claim ~~116~~ wherein:
each of said first and second biasing means includes over-center spring means.

¹⁰⁶ ¹⁰⁴
CLAIM ~~118~~. An oscillating sprinkler unit as in claim ~~116~~ wherein:
one of said first and second biasing means includes spring means for imposing a load on said shiftable carrier, and the other of said biasing means includes spring means for imposing a load on said shift means.

~~103~~
104

107
CLAIM ~~119~~. A rotary drive sprinkler device comprising:

a housing for receiving a supply of water;

nozzle head means for directing the flow of water from the sprinkler device,
said nozzle head means having a top;

rotatable output shaft means in said housing, said output shaft means being
drivingly connected to said nozzle head means;

a drive assembly in said housing for driving said output shaft means;

reversing means within said housing for reversing the direction of rotation of
said output shaft means to oscillate said nozzle head means;

actuation means connected to said reversing means for operating said
reversing means;

first and second angular limit contact means within said housing for defining
a desired angle of oscillation of said nozzle head means, at least one of said contact
means being adjustable with respect to the other to set a desired angle of oscillation
of said nozzle head means;

said actuation means being responsive to contact with each of said first and
second said angular limit contact means to actuate said reversing means to reverse
the direction of rotation of said output shaft means;

setting means at the top of said nozzle head means connected to at least one
of said angular limit contact means within said housing for changing the relative
angular position between said first and second angular limit contact means to
increase or decrease the angle of oscillation; and

indicator means at the top of said nozzle head means for providing a visual
representation of a change in angle of oscillation.

104
105

¹⁰⁸
CLAIM ~~120~~. A rotary drive sprinkler device as in claim ¹⁰⁷~~119~~ including:

indicating means on the exterior of said nozzle means for indicating the direction the setting means should be moved to increase or decrease the angle of oscillation.

¹⁰⁹
CLAIM ~~121~~. A rotary drive sprinkler device as in claim ¹⁰⁷~~119~~ wherein:

said nozzle means has a top surface; and

said setting means is located in the center of the top surface.

¹¹⁰
CLAIM ~~122~~. A rotary drive sprinkler device as in claim ¹⁰⁷~~119~~ wherein:

EG
said setting means is directly accessible and actuated from the exterior of said nozzle means.

¹¹¹
CLAIM ~~123~~. A rotary drive sprinkler device as in claim ¹⁰⁷~~119~~, wherein:

said nozzle means has a top surface; and

said setting means and said indicator means are located in the center of said top surface.

¹¹²
CLAIM ~~124~~. A rotary drive sprinkler device as in claim ¹¹¹~~123~~ wherein:

said setting means forms part of said indicating means.

¹¹³
CLAIM ~~125~~. A rotary drive sprinkler device as in claim ¹⁰⁷~~119~~ wherein:

said setting means on the top of said nozzle head means is rotatable; and

the degree of rotation of said setting means is equal to the degree of change in angular position between said first and second angular limit contact means.

24

¹¹⁴
CLAIM 126. A rotary drive sprinkler device as in claim ¹⁰⁷~~119~~ including:

indicator means on the top of nozzle head means for indicating the position
of a nozzle in said nozzle head means.

~~106~~
117

115
CLAIM 127. A rotary drive sprinkler device comprising:

a housing for receiving a supply of water;

nozzle head means for directing the flow of water from the sprinkler device,
said nozzle head means having a top;

rotatable output shaft means in said housing, said output shaft means being
drivingly connected to said nozzle head means;

E4
a drive assembly in said housing for driving said output shaft means;

reversing means within said housing for reversing the direction of rotation of
said output shaft means to oscillate said nozzle head means;

actuation means connected to said reversing means for operating said
reversing means;

first and second angular limit contact means within said housing for defining
a desired angle of oscillation of said nozzle head means, at least one of said contact
means being adjustable with respect to the other to set a desired angle of oscillation
of said nozzle head means;

said actuating means being responsive to contact with each of said first and
second said angular limit contact means to actuate said reversing means to reverse
the direction of rotation of said output shaft means;

rotatable setting means in said nozzle head means connected to at least one of
said angular limit contact means within said housing for changing the relative
angular position between said first and second angular limit contact means to
increase or decrease the angle of oscillation by an amount substantially equal to the
rotation of said setting means; and

said nozzle head means having a top surface and said setting means being at
the center of said top surface and being accessible from the exterior of said nozzle.

¹¹⁶
CLAIM ~~128~~. A rotary drive sprinkler device as in claim ~~127~~,¹¹⁵ including:

indicator means on said top surface having indicia representative of changes in the angle of oscillation of said nozzle head means;

said setting means cooperating with said indicia to provide a visual representation of a change in angle of oscillation.

¹¹⁷
CLAIM ~~129~~. A rotary drive sprinkler device as in claim ~~127~~¹¹⁵ wherein said indicator means includes:

indicia on the exterior of said nozzle means for indicating the direction the setting means should be moved to increase or decrease the angle of oscillation.

¹¹⁷
CLAIM ~~130~~. A rotary drive sprinkler device as in claim ~~129~~¹¹⁷ wherein:

said setting means includes a slot which cooperates with said indicia to provide a visual representation of a change in angle of oscillation.

¹¹⁹
CLAIM ~~131~~. A rotary drive sprinkler device as in claim ~~130~~¹¹⁷ wherein:

said setting means is directly accessible and actuated from the exterior of said nozzle means.

¹²⁰
CLAIM ~~132~~. A rotary drive sprinkler device as in claim ~~131~~¹¹⁹ wherein:

said setting means forms part of said indicator means.

¹²¹
CLAIM ~~133~~. A rotary drive sprinkler device as in claim ~~129~~¹¹⁷ wherein:

said setting means includes a slot which cooperates with said indicia to provide a visual representation of a change in angle of oscillation.

¹²²
CLAIM ~~134~~. A rotary drive sprinkler device as in claim ~~127~~ ¹¹⁵ wherein:

said setting means on the top of said nozzle head means is rotatable; and
the degree of rotation of said setting means is equal to the degree of change
in angular position between said first and second angular limit contact means.

¹²³
CLAIM ~~135~~. A rotary drive sprinkler device as in claim ~~127~~ ¹¹⁵ including:

indicator means on the top of nozzle head means for indicating the position
of a nozzle in said nozzle head means.

~~100~~ 110

124
CLAIM 436. A rotary drive sprinkler device comprising:

a housing for receiving a supply of water;

nozzle head means for directing the flow of water from the sprinkler device,

said nozzle head means having a top;

rotatable output shaft means in said housing, said output shaft means being drivingly connected to said nozzle head means;

E4
a drive assembly in said housing for driving said output shaft means;

reversing means within said housing for reversing the direction of rotation of said output shaft means to oscillate said nozzle head means;

actuation means connected to said reversing means for operating said reversing means;

first and second angular limit contact means within said housing for defining a desired angle of oscillation of said nozzle head means, at least one of said contact means being adjustable with respect to the other to set a desired angle of oscillation of said nozzle head means;

said actuation means being responsive to contact with each of said first and second said angular limit contact means to actuate said reversing means to reverse the direction of rotation of said output shaft means;

setting means at the top and center of said nozzle head means connected to at least one of said angular limit contact means within said housing for changing the relative angular position between said first and second angular limit contact means to increase or decrease the angle of oscillation; and

indicator means at the top of said nozzle head means for providing a visual representation of the angle of oscillation which has been set.

¹²⁵
CLAIM ~~137~~. A rotary drive sprinkler device as in claim ~~136~~¹²⁴ including:

indicating means on the exterior of said nozzle means for indicating the direction the setting means should be moved to increase or decrease the angle of oscillation.

¹²⁶
CLAIM ~~138~~. A rotary drive sprinkler device as in claim ~~136~~¹²⁴ wherein:

said nozzle means has a top surface; and

said setting means is located in the center of the top surface.

¹²⁷
CLAIM ~~139~~. A rotary drive sprinkler device as in claim ~~136~~¹²⁴ wherein:

said setting means is accessible and actuated from the exterior of said nozzle means.

¹²⁸
CLAIM ~~140~~. A rotary drive sprinkler device as in claim ~~136~~¹²⁴ wherein:

said setting means on the top of said nozzle head means is rotatable; and the degree of rotation of said setting means is equal to the degree of change in angular position between said first and second angular limit contact means.

¹²⁹
CLAIM ~~141~~. A rotary drive sprinkler device as in claim ~~136~~¹²⁴ including:

indicator means on the top of nozzle head means for indicating the position of a nozzle in said nozzle head means.

¹³⁰
CLAIM ~~142~~. A rotary drive sprinkler device as in claim ~~136~~¹²⁴ wherein:

said setting means forms part of said indicating means.

¹³¹
CLAIM ~~143~~. A rotary drive sprinkler device as in claim ¹²⁹~~130~~ wherein said indicator means includes:

E4 indicia on the exterior of said nozzle means for indicating the direction the setting means should be moved to increase or decrease the angle of oscillation.

¹³²
CLAIM ~~144~~. A rotary drive sprinkler device as in claim ¹³¹143 wherein:

said setting means includes a slot which cooperates with said indicia to provide a visual representation of a change in angle of oscillation.

112 113

133
CLAIM 145. A rotary drive sprinkler device comprising:

a housing for receiving a supply of water;

nozzle head means for directing the flow of water from the sprinkler device,

said nozzle head means having a top;

rotatable output shaft means in said housing, said output shaft means being
drivingly connected to said nozzle head means;

a drive assembly in said housing for driving said output shaft means;

reversing means within said housing for reversing the direction of rotation of
said output shaft means to oscillate said nozzle head means;

actuation means connected to said reversing means for operating said
reversing means;

first and second angular limit contact means for defining a desired angle of
oscillation of said nozzle head means, at least one of said contact means being
adjustable with respect to the other to set a desired angle of oscillation of said nozzle
head means;

said actuation means being responsive to contact with each of said first and
second said angular limit contact means to actuate said reversing means to reverse
the direction of rotation of said output shaft means;

setting means at the top of said nozzle head means for changing the relative
angular position between said first and second angular limit contact means to
increase or decrease the angle of oscillation, said setting means being above said
angular limit contact means and being connected to at least one of said angular limit
contact means; and

indicator means at the top of said nozzle head means for providing a visual
representation of a change in angle of oscillation.

¹³⁴
CLAIM ~~146~~. A rotary drive sprinkler device as in claim ~~145~~ ¹³³ including:

indicating means on the exterior of said nozzle means for indicating the direction the setting means should be moved to increase or decrease the angle of oscillation.

¹³⁵
CLAIM ~~147~~. A rotary drive sprinkler device as in claim ~~145~~ ¹³³ wherein:

said nozzle means has a top surface; and

said setting means is located in the center of the top surface.

¹³⁶
CLAIM ~~148~~. A rotary drive sprinkler device as in claim ~~145~~ ¹³³ wherein:

said setting means is directly accessible and actuated from the exterior of said nozzle means.

¹³⁷
CLAIM ~~149~~. A rotary drive sprinkler device as in claim ~~145~~ ¹³³, wherein:

said nozzle means has a top surface; and

said setting means and said indicator means are located in the center of said top surface.

¹³⁸
CLAIM ~~150~~. A rotary drive sprinkler device as in claim ~~149~~ ¹³⁷ wherein:

said setting means forms part of said indicating means.

139
CLAIM ~~151~~. A rotary drive sprinkler device as in claim ~~145~~ wherein:

34
said setting means on the top of said nozzle head means is rotatable; and
the degree of rotation of said setting means is equal to the degree of change
in angular position between said first and second angular limit contact means.

140
CLAIM ~~152~~. A rotary drive sprinkler device as in claim ~~145~~ including:

137
indicator means on the top of nozzle head means for indicating the position
of a nozzle in said nozzle head means.

141
CLAIM 153. A rotary drive sprinkler device comprising:

a housing for receiving a supply of water;

nozzle head means for directing the flow of water from the sprinkler device,
said nozzle head means having a top;

rotatable output shaft means in said housing, said output shaft means being
drivingly connected to said nozzle head means;

a drive assembly in said housing for driving said output shaft means;

reversing means within said housing for reversing the direction of rotation of
said output shaft means to oscillate said nozzle head means;

actuation means connected to said reversing means for operating said
reversing means;

first and second angular limit contact means for defining a desired angle of
oscillation of said nozzle head means, at least one of said contact means being
adjustable with respect to the other to set a desired angle of oscillation of said nozzle
head means;

said actuating means being responsive to contact with each of said first and
second said angular limit contact means to actuate said reversing means to reverse
the direction of rotation of said output shaft means;

rotatable setting means in said nozzle head means for changing the relative
angular position between said first and second angular limit contact means to
increase or decrease the angle of oscillation by an amount substantially equal to the
rotation of said setting means, said rotatable setting means being above said angular
limit contact means and being connected to at least one of said angular limit contact
means; and

116
117

said nozzle head means having a top surface and said setting means being at the center of said top surface and being accessible from the exterior of said nozzle.

¹⁴²
CLAIM ~~154~~. A rotary drive sprinkler device as in claim ~~153~~¹⁴¹, including:

indicator means on said top surface having indicia representative of changes in the angle of oscillation of said nozzle head means;

said setting means cooperating with said indicia to provide a visual representation of a change in angle of oscillation.

¹⁴³
CLAIM ~~155~~. A rotary drive sprinkler device as in claim ~~153~~¹⁴¹ wherein said indicator means includes:

indicia on the exterior of said nozzle means for indicating the direction the setting means should be moved to increase or decrease the angle of oscillation.

¹⁴⁴
CLAIM ~~156~~. A rotary drive sprinkler device as in claim ~~155~~¹⁴³ wherein:

said setting means includes a slot which cooperates with said indicia to provide a visual representation of a change in angle of oscillation.

¹⁴⁵
CLAIM ~~157~~. A rotary drive sprinkler device as in claim ~~156~~¹⁴⁴ wherein:

said setting means is directly accessible and actuated from the exterior of said nozzle means.

¹⁴⁶
CLAIM ~~158~~. A rotary drive sprinkler device as in claim ~~157~~¹⁴⁵ wherein:

said setting means forms part of said indicator means.

¹⁴⁷
CLAIM ~~159~~. A rotary drive sprinkler device as in claim ¹⁴³~~153~~ wherein:

said setting means includes a slot which cooperates with said indicia to provide a visual representation of a change in angle of oscillation.

¹⁴⁸
CLAIM ~~160~~. A rotary drive sprinkler device as in claim ¹⁴¹~~153~~ wherein:

said setting means on the top of said nozzle head means is rotatable; and the degree of rotation of said setting means is equal to the degree of change in angular position between said first and second angular limit contact means.

¹⁴⁹
CLAIM ~~161~~. A rotary drive sprinkler device as in claim ¹⁴¹~~153~~ including:

indicator means on the top of nozzle head means for indicating the position of a nozzle in said nozzle head means.

118
119

150
CLAIM 162. A rotary drive sprinkler device comprising:

a housing for receiving a supply of water;

nozzle head means for directing the flow of water from the sprinkler device,
said nozzle head means having a top;

rotatable output shaft means in said housing, said output shaft means being
drivingly connected to said nozzle head means;

Eg
a drive assembly in said housing for driving said output shaft means;

reversing means within said housing for reversing the direction of rotation of
said output shaft means to oscillate said nozzle head means;

actuation means connected to said reversing means for operating said
reversing means;

first and second angular limit contact means for defining a desired angle of
oscillation of said nozzle head means, at least one of said contact means being
adjustable with respect to the other to set a desired angle of oscillation of said nozzle
head means;

said actuation means being responsive to contact with each of said first and
second said angular limit contact means to actuate said reversing means to reverse
the direction of rotation of said output shaft means;

setting means at the top and center of said nozzle head means for changing
the relative angular position between said first and second angular limit contact
means to increase or decrease the angle of oscillation, said setting means being
above said angular limit contact means and being connected to at least one of said
angular limit contact means; and

indicator means at the top of said nozzle head means for providing a visual
representation of the angle of oscillation which has been set.

¹⁵¹
CLAIM ~~163~~. A rotary drive sprinkler device as in claim ¹⁵⁰~~162~~ including:

indicating means on the exterior of said nozzle means for indicating the direction the setting means should be moved to increase or decrease the angle of oscillation.

¹⁵²
CLAIM ~~164~~. A rotary drive sprinkler device as in claim ¹⁵⁰~~162~~ wherein:

said nozzle means has a top surface; and

said setting means is located in the center of the top surface.

¹⁵³
CLAIM ~~165~~. A rotary drive sprinkler device as in claim ¹⁵⁰~~162~~ wherein:

said setting means is accessible and actuated from the exterior of said nozzle means.

¹⁵⁴
CLAIM ~~166~~. A rotary drive sprinkler device as in claim ¹⁵⁰~~162~~ wherein:

said setting means on the top of said nozzle head means is rotatable; and

the degree of rotation of said setting means is equal to the degree of change in angular position between said first and second angular limit contact means.

¹⁵⁵
CLAIM ~~167~~. A rotary drive sprinkler device as in claim ¹⁵⁰~~162~~ including:

indicator means on the top of nozzle head means for indicating the position of a nozzle in said nozzle head means.

¹⁵⁶
CLAIM ~~168~~. A rotary drive sprinkler device as in claim ¹⁵⁰~~162~~ wherein:

said setting means forms part of said indicating means.

¹⁵⁷
CLAIM ~~169~~. A rotary drive sprinkler device as in claim ¹⁵⁰~~162~~ wherein said indicator means includes:

indicia on the exterior of said nozzle means for indicating the direction the setting means should be moved to increase or decrease the angle of oscillation.

¹⁵⁷
CLAIM ~~170~~. A rotary drive sprinkler device as in claim ¹⁵⁷~~169~~ wherein:

EG
said setting means includes a slot which cooperates with said indicia to provide a visual representation of a change in angle of oscillation.

¹⁵⁷
CLAIM ~~171~~. An oscillating sprinkler unit, comprising: a sprinkler head mounted for rotation about a first axis; drive means including a shiftable carrier for alternately engageable driving positions with rotating drive means for driving said sprinkler head in alternate directions; shifting arm means pivotally movable by arc control contact means for shifting said carrier towards one or the other of said alternately engageable driving positions; and biasing means for placing said shiftable carrier in driving engagement and for retaining said shiftable carrier in a selected one of said alternately engageable driving positions until shifted therefrom by said shifting arm means.

¹⁶⁰
CLAIM ~~172~~. An oscillating sprinkler unit as in claim ¹⁵⁹~~171~~ wherein:

said biasing means retains said shiftable carrier in one or the other of said alternately engageable driving positions with said rotating drive means until shifted therefrom by said shifting arm means in response to engagement of said shifting arm means by said arc control contact means.